

motech[®]

refrigeration parts and equipment



Data Sheet

BASIC DATA

1.1 OPERATION

Application: LBP

Refrigerant: R134a

Expansion device: Capillary tube

Cooling: Static

Evaporating Temperature Range: -35 to -10°C (-34 to +14 °F)

Max Ambient Temperature: 43°C (110°F)

Max Operating Discharge Temperature(1): 120°C (248°F)

Max Peak Discharge Temperature (1, 2): 135°C (275°F)

Max Operating Condensing Temperature: 60°C (140°F)

Max Peak Condensing Temperature(2): 70°C (158°F)

Max Winding Temperature: 130°C (266°F)

Max Impurities: 30 mg

Max Water Content: 100 mg

1.2 COMPRESSOR

Displacement: 7.5 cc

Cylinder Bore: 23.6 mm

Stroke: 17.2mm

Net Weight(3): 8.6 Kg

Shell size: Middle

Oil charge: 200 cc

Oil Type: ICI RL 9EB

Oil viscosity(4): 9 cSt

Suction system: Semi-direct

1.3 MOTOR

Power supply: 220-240 V

Voltage limits: 187 - 264 V

Frequency: 50 Hz

Phase: 1

Motor Type: RSIR / RSCR

Electrical Insulation Class: B

Locked Rotor Current at 220 V- Max value with RC:

Locked Rotor Current at 220 V- After 4 s with RC:

Locked Rotor Current at 220 V- Max value without RC:

Locked Rotor Current at 220 V- After 4 s without RC:

Main Winding Resistance at 20°C (68°F): 13.00 Ω

Start Winding Resistance at 20°C (68°F): 13.50 Ω

(1) Measured at 5 cm from the shell with insulated termocouples

(2) For transient conditions during "Pull Down"

(3) With oil and without external electricals

(4) Measured at 40°C (104°F)

1.4 ELECTRICALS

Motor-protector

Manufacturer: WANBAO
Type: BT90-120A61D2
Open Temperature: 115-125 °C
Close Temperature: 70-52 °C
U.T.C. at 70°C: 1.96 A
Time Check Current 7-15 s: 9.0 A (7.5-14 sec)
Max Current: -
Code: -

PTC starting device

Assembly type:	WANBAO	TIANYIN
PTC Pill:	QP2-15	QP2-15E
Resistance at 25°C, 100V:	11-19Ω	11-19Ω
V max:	350 V	350 V
I max:	8A	8A
Curie Temp:	120°C	120°C
Dimensions:	20mm (diameter), 3.3mm (thickness)	16mm (diameter), 2.5mm (thickness)

Run capacitor (optional)

Type: plastic case
Capacity: 4μF
Vmax: 450 V
Working hours: 10.000 h at 450 V

Connecting-board

Type: Without
Fast-on size

CALORIMETER DATA

2.1 CALORIMETER TEST	Evaporating temperature					
	-30°C	-23.3°C	-10°C	-30°C	-23.3°C	-10°C
	Without RC			With RC		
Cooling capacity (W)		215			215	
Input power (W)		147			156	
COP (W)/W		1.46			1.38	
Current (A)		0.83			1.15	

Test conditions according to ASHRAE:

Condensing temperature: +55°C(+130°F)
Subcooling temperature: +32°C(+90°F)
Superheating temperature: +32°C(+90°F)
Suction temperature: +32°C(+90°F)

Room temperature: +32°C(+90°F)

Cooling: Static cooling
Supply Voltage: 220 V
Supply Frequency: 50 Hz
Run capacitor: 4μF

OTHER PERFORMANCES

3.1 STARTING TEST	Motor Temp. / Equalized Press.		
	90°C / 5 Bar A	43°C / 6.5 Bar A	25°C / 5 Bar A
Min. Starting Voltage (V)	160		

According to ACC-CQ-PRO-99016.D

3.2 CALORIMETER TEST	-25/+55°C	-20/+50°C	-23.3/+40°C
	ISO3745	GB9098	USA STD
A-weighted SPL (dBA)	-	42	-
Vibration Level (dB)	-	-	-
Vibration Index TVI (mm/s)	-	0.6	-
Gas pulse level TPI (mBar)	-	-	-

3.3 LIFE TEST	Wear	High Temp.	On Off
	500 h	2000 h	200 K Cycles
Test Results	Passed	Passed	Passed

Wear Test according to CECOMAF GT4003

High Temperature Test according to CECOMAF GT4002

On Off Test according to CECOMAF GT4004

3.4 TRANSPORT TEST	2 h - 0.75 m/s ²		
	x - 3.25 Hz	y - 7.5 Hz	z - 11.5 Hz
Test Results		Not required	

According to GB / T4857.10-92

3.5 OIL TRANSPORT TEST	Oil flow
	(g/h)
Test Results	Not required

According to ACC-CQ-ES-99002.D

3.6 IMPACT TEST	
Test Results	Not required

According to ECC-CQ-W-01042